



# ProTalk<sup>®</sup>LT PKT-23

## Pocket-Sized UHF CB Portable Radio

### A Powerful Business Radio in the Palm of Your Hand

At just 110g, KENWOOD's PKT-23 UHF CB two-way radio packs a lot of performance for its size: 1.5 watts of transmit power, preset CB 80 channels, and up to 15 hours of operation. It's simple to use and you can plug KENWOOD headphones into the 3.5mm audio jack for hands-free operation. A micro USB socket offers charging convenience. And since this radio is classed as CBRS, no licence is required. Plus, the PKT-23 is built tough for business and leisure, meeting or exceeding MIL-Spec 810 C/D/E/F/G (11 items) and IP54 (dust/water intrusion) standards.



Actual Size

### General Features

- 1.5 Watts of Transmit Power
- Preset CB 80 Channels
- 8 Memory Channels
- 50 CTCSS/104 DCS (Coded Squelch)
- Super Lock (Manager Key Lock)
- Scan Function
- 2 PF KeysEnhanced KENWOOD Audio
- Micro USB Port
- VOX ReadyVoice Announcement
- Bell Tone Alert
- LED Battery Status Indicator
- IP54 & MIL-STD 810 C/D/E/F/G 11 items
- Battery Saver
- Time Out Timer
- Monitor
- Wireless Clone

### ACCESSORIES INCLUDED

- KNB-71L - 1,430mAh Li-Ion
- USB Cable for Charge
- KBH-20 - Belt Clip
- Owner's Manual

### COMMUNICATION DISTANCE

Conditions	Distance
Open areas without obstructions	Up to 8 km
Residential areas (near buildings)	Up to 2.4 km
In steel and/or concrete reinforced building	Up to 20,900 sq.m
In high-rise buildings	Up to 17floors

*Note:  
Talk range will vary based on terrain and contions.*

For more information talk to our experts on  
02 9792 4188 or email [sales@btgau.com.au](mailto:sales@btgau.com.au)

# Options

■ **KNB-71L**  
Li-Ion Battery  
(1,430 mAh)



■ **KHS-33**  
Earbud In-line  
PTT Headset  
(Single Pin Jack)



■ **KHS-34**  
C-Ring In-line  
PTT Headset  
(Single Pin Jack)



■ **KBH-20**  
Spring Action  
Belt Clip



All accessories and options may not be available in all markets.  
Contact an authorised KENWOOD dealer for details and complete list of all accessories and options.

## Specifications

Model	PKT-23
<b>GENERAL</b>	
Frequency Range	476.425-477.4125 MHz
CB	Preset 80 Channels
Number of Memory Channels	8
Channel Spacing	12.5 kHz
Operating Voltage	3.8V DC±10%
Battery Life (5-5-90 duty cycle) with KNB-71L (1,430mAh)	Approx. 11 hours (Battery saver off) Approx. 15 hours (Battery saver on)
Operating Temperature Range	-10°C ~ +60°C
Frequency Stability	±2.5ppm
Antenna Impedance	50 Ω
Dimensions (W x H x D), Projections not Included	
Radio with KNB-71L	46.0 x 85.0 x 21.0 mm
Weight (net)	
Radio with KNB-71L	110 g

Model	PKT-23
<b>RECEIVER (Measurements made per TIA-603)</b>	
Sensitivity (12dB SINAD)	0.22 μV
Selectivity	60 dB
Intermodulation Distortion	50 dB
Audio Output	300 mW with less than 5% distortion
<b>TRANSMITTER (Measurements made per TIA-603)</b>	
RF Output Power	
High	1.5 W (ERP)
Low	0.5 W (ERP)
Spurious Response	55 dB
Modulation	11KØF3E
FM Hum & Noise	50 dB
Audio Distortion	Less than 5%

Specifications shown are typical.  
Specifications are subject to change without notice, due to advancements in technology.

ProTalk® is a registered trademark of JVCKENWOOD Corporation in the United States and other countries.

## Applicable MIL-STD & IP

Standard	MIL 810C Methods/Procedures	MIL 810D Methods/Procedures	MIL 810E Methods/Procedures	MIL 810F Methods/Procedures	MIL 810G Methods/Procedures
Low Pressure	500.1/Procedure I	500.2/Procedure I, II	500.3/Procedure I, II	500.4/Procedure I, II	500.5/Procedure I, II
High Temperature	501.1/Procedure I, II	501.2/Procedure I, II	501.3/Procedure I, II	501.4/Procedure I, II	501.5/Procedure I, II
Low Temperature	502.1/Procedure I	502.2/Procedure I, II	502.3/Procedure I, II	502.4/Procedure I, II	502.5/Procedure I, II
Temperature Shock	503.1/Procedure I	503.2/Procedure I	503.3/Procedure I	503.4/Procedure I, II	503.5/Procedure I
Solar Radiation	505.1/Procedure I	505.2/Procedure I	505.3/Procedure I	505.4/Procedure I	505.5/Procedure I
Rain	506.1/Procedure I, II	506.2/Procedure I, II	506.3/Procedure I, II	506.4/Procedure I, III	506.5/Procedure I, III
Humidity	507.1/Procedure I, II	507.2/Procedure II, III	507.3/Procedure II, III	507.4	507.5/Procedure II
Salt Fog	509.1/Procedure I	509.2/Procedure I	509.3/Procedure I	509.4	509.5
Dust	510.1/Procedure I	510.2/Procedure I	510.3/Procedure I	510.4/Procedure I, III	510.5/Procedure I
Vibration	514.2/Procedure VIII, X	514.3/Procedure I	514.4/Procedure I	514.5/Procedure I	514.6/Procedure I
Shock	516.2/Procedure I, II, V	516.3/Procedure I, IV	516.4/Procedure I, IV	516.5/Procedure I, IV	516.6/Procedure I, IV
<b>International Protection Standard</b>					
Dust & Water Protection	IP54				

\*To meet MIL 810 and IP grade, the 3.5mm phone jack has to be sealed by the rubber cover or connected to KENWOOD headset KHS-33 or KHS-34.  
The micro USB jack has to be sealed by the rubber cover, and the battery has to be sealed by the cover.

**BRIGHTON TECHNOLOGIES GROUP**  
8/31 Maclaurin Ave, East Hills NSW 2213  
Phone: 02 9792 4188 Email: sales@btgau.com.au  
www.btgau.com.au

