

MEIKO UPster® U - Undercounter / UPster® H - Hood Type



The clean solution

Glass and dishwashers

The UPster range offers user friendly technology at an economical price.
All machines are double skin insulated to reduce heat and noise emissions.

UPster® U 400



Entry height
H 300 mm
Dimensions
H 845 mm
(725mm
with removal
of plinth)
W 460 mm, D 600 mm
Rack dimensions
400 x 400 mm
Cycle Times
120/180/240 secs
Litres Per Cycle
2.2 L
Power
240V 50Hz, 2.8 kW,
15 amp – Single Phase
Water
Hot – Max 60 degrees

UPster® U 500



Entry height
H 320 mm
Dimensions
H 845 mm,
W 600 mm, D 600 mm
Rack dimensions
500 x 500 mm
Cycle Times
120/180/240 secs
Litres Per Cycle
3 L
Power
240V 50Hz, 2.8 kW,
15 amp – Single Phase
Water
Hot – Max 60 Degrees

UPster® H 500



Entry height
H 440 mm
Dimensions
H 2050/2288* mm,
W 635 mm, D 750 mm
*with optional AirBox
Rack dimensions
500 x 500 mm
Cycle Times
60/90/150/240 secs
Litres Per Cycle
3 L
Power
415V 50Hz, 8.5Kw, 12
amp – 3 phase
Water
Hot – Max 60 degrees
Option: Airbox

Standard Features - All Models

- FULLY INSULATED CHAMBER AND DOORS
- TOUCH PAD LOW VOLTS
- MEIKO ECO FILTERING FROM THE BOTTOM OF THE WASH TANK
- SOFT START ON THE WASH PUMP (UNDERCOUNTER)
- SPRING ASSISTED DOOR
- MACHINE SWITCHES TO ECO MODE IF NOT IN USE
- MACHINE EQUIPPED WITH PUMP OUT DRAIN
- MACHINE COMES WITH COMPLETE INSTALLATION KIT
- DETERGENT RINSE AID PUMP
- CONTROL PANEL SET UP FOR INFRARED INTERFACE
- SELF CLEANING PROGRAM WHEN EMPTYING MACHINE
- MACHINE COMPLETE WITH REAR PANEL
- WASH MANIFOLD RUNS UP THE BACK OF THE MACHINE AND NOT IN THE TANK
- H500 HOOD SLOPED INTERNALLY TO STOP WATER DRIPPING ON THE OPERATOR
- MACHINE DRAINS BEFORE IT RINSES
- MACHINE HAS RINSE TEMPERATURE SAFETY FEATURE

MEIKO M-iClean U - Undercounter



The clean solution

Glass, Dish and Utensil Washers

The M-iClean range sets new standards in technology design and ease of use.

The undercounter machines are equipped with LED handle and brightly lit interiors.

M-iClean US



Entry Height
H 315 mm
Dimensions
H 835-855 mm, W 460 mm,
D 600 mm
Rack Dimensions
400 x 400 mm
Cycle Times
90/120/180 secs
Litres Per Cycle
1.9 L
Power
240V 50Hz, 2.7kW,
15 amp single phase
Or
415V 50Hz, 6.8kW, 9.5 amp
3 phase
Water
Hot – Max 60 degrees
Cold with GiO or AC
Optional Extras:
• M-iClean AirConcept
(heat recovery)
• MEIKO GiO MODULE
technology with Reverse
Osmosis

M-iClean UM



Entry Height
H 315 mm
Dimensions
H 835-855 mm, W 600 mm,
D 600 mm
Rack Dimensions
500 x 500 mm
Capacity
90/120/180 secs
Litres Per Cycle
2.4 L
Power
240V 50Hz, 6.8kW,
15 amp single phase
Or
415V 50Hz, 6.7kW, 9.5 amp
3 phase
Water
Hot – Max 60 degrees
Cold with GiO or AC
Optional Extras:
• M-iClean AirConcept
(heat recovery)
• MEIKO GiO MODULE
technology with Reverse
Osmosis

M-iClean UM+



Entry Height
H 435 mm
Dimensions
H 820-855 mm, W 600 mm,
D 600 mm
Rack Dimensions
500 x 500 mm
Cycle Times
90/120/180 secs
Litres Per Cycle
2.4 L
Power
240V 50Hz, 2.7kW,
15 amp single phase
Or
415V 50Hz, 6.7kW, 9.5 amp
3 phase
Water
Hot – Max 60 degrees
Cold with GiO or AC
Optional extras:
• M-iClean AirConcept
(heat recovery)
• MEIKO GiO MODULE
technology with Reverse
Osmosis

M-iClean UL



Entry height
H 435 mm
Dimensions
H 820-855 mm, W 600 mm,
D 680 mm
Rack dimensions
500 x 500 mm
to 600 x 500 mm
Cycle Times
90/120/180 secs
Litres Per Cycle
2.8 L
Power
240V 50Hz, 6.7kW,
15 amp single phase
Or
415V 50Hz, 6.7kW, 9.5 amp
3 phase
Water
Hot – Max 60 degrees
Cold with GiO or AC
Optional Extras:
• M-iClean AirConcept
(heat recovery)
• MEIKO GiO MODULE
technology with Reverse
Osmosis

Standard Features - All Models

- FULLY INSULATED CHAMBER AND DOORS
- TOUCH SCREEN CONTROL WITH MESSAGES IN ENGLISH
- MEIKO ACTIVE FILTERING OF THE WASH TANK
- SOFT START ON THE WASH PUMP
- ILLUMINATED HANDLE WITH COLOUR STATUS
- CYCLE PROGRESS ON THE DISPLAY PANEL
- LED LIGHT INTO THE CHAMBER
- SPRING ASSISTED DOOR
- DOOR AJAR STOP POSITION
- MACHINE SWITCHES TO ECO MODE IF NOT IN USE
- EQUIPPED WITH AQUA STOP LEAKAGE DETECTION
- MACHINE EQUIPPED WITH PUMP OUT DRAIN
- MACHINE COMES WITH COMPLETE INSTALLATION KIT
- CONTROL PANEL SET UP FOR BLUE TOOTH CONNECTION
- STAINLESS STEEL CHEMICAL PIPES WITHIN THE MACHINE
- STAINLESS STEEL WASH AND RINSE MANIFOLD UP THE BACK OF THE MACHINE
- FINAL DRAIN PUMP FILTER
- SELF CLEANING PROGRAM WHEN EMPTYING MACHINE
- COMBINED WASH AND RINSE ARM
- MACHINE COMPLETE WITH REAR PANEL
- OPTION OF THE GiO REVERSE OSMOSIS MODULE
- WASH MANIFOLD RUNS UP THE BACK OF THE MACHINE AND NOT IN THE TANK
- MACHINE DRAINS BEFORE IT RINSES
- MACHINE HAS RINSE TEMPERATURE SAFETY FEATURE



MEIKO M-iClean H - Hood Type

Hood type dishwashing systems

M-iClean HM



Entry Height
H 505 mm
Rack Dimensions
500 x 500 mm
Cycle Times
60/90/210 secs
Litres Per Cycle
2.4 L
Power
415V 50Hz, 9.1 kW, 15.9 amp
3 phase
Water
Hot - Max 60 degrees
Cold with GiO or AC
Optional Extras:
• AirConcept exhaust heat recovery –
• MEIKO GiO MODULE technology with Reverse Osmosis

M-iClean HL



Entry Height
H 560 mm
Rack Dimensions
500 x 500 mm
to 600 x 500 mm
Cycle Times
60/90/210 secs
Litres Per Cycle
3 L
Power
415V 50Hz, 9.8 kW, 16.3 amp
3 phase
Water
Hot - Max 60 degrees
Cold with GiO or AC
Optional Extras:
• AirConcept exhaust heat recovery –
• MEIKO GiO MODULE technology with Reverse Osmosis

M-iClean HXL



Entry Height
H 505 mm
Rack Dimensions
2 x 500 x 500 mm
Cycle Times
60/90/210 secs
Litres Per Cycle
4.8 L
Power
415V 50Hz, 20.1 kW,
31 amp 3 phase
Water
Hot - Max 60 degrees
Cold with GiO or AC
Optional Extras:
• AirConcept exhaust heat recovery
• MEIKO GiO MODULE technology with Reverse Osmosis

Standard Features - All Models

- AUTOMATIC HOOD
- AUTOMATIC RACK DETECTION
- FULLY INSULATED CHAMBER AND DOORS
- TOUCH SCREEN CONTROL WITH MESSAGES IN ENGLISH
- MEIKO ACTIVE FILTERING OF THE WASH TANK
- CYCLE PROGRESS ON THE DISPLAY PANEL
- MACHINE SWITCHES TO ECO MODE IF NOT IN USE
- EQUIPPED WITH AQUA STOP LEAKAGE DETECTION
- MACHINE EQUIPPED WITH PUMP OUT DRAIN
- MACHINE COMES WITH COMPLETE INSTALLATION KIT
- CONTROL PANEL SET UP FOR BLUE TOOTH CONNECTION
- STAINLESS STEEL CHEMICAL PIPES WITHIN THE MACHINE
- STAINLESS STEEL WASH AND RINSE MANIFOLD UP THE BACK OF THE MACHINE
- FINAL DRAIN PUMP FILTER
- SELF CLEANING PROGRAM WHEN EMPTYING MACHINE
- COMBINED WASH AND RINSE ARM
- MACHINE COMPLETE WITH REAR PANEL
- OPTION OF THE GiO REVERSE OSMOSIS MODULE
- MACHINE DRAINS BEFORE IT RINSES
- MACHINE HAS RINSE TEMPERATURE SAFETY FEATURE

Brightwash
Machines | Chemicals | Service



Visit our website:
www.btgau.com.au



Send an email:
sales@btgau.com.au



Give us a call:
1300 367 177